# **OPTILUX**

# Mirror front lamp

Product Code
ARCIMFL1A24W220V



IP rating 54
Ik rating 5

**Source type** Hight power LED

**Source life time** >50,000h at 25°C ambient temperature

CRI >80 Step McAdam 3

Source flux

Source efficiency

Delivered flux

Delivered efficiency

Input power

Supply voltage

2880 lm

120 lm/W

120 lm/W

2400 lm

24W

24W

24W

**Insulation Class** insulation class III

Power supply -

Material Aluminum+PC


Light colour/CCT 3000K

Beam angle diffuse

**Mounting** surface mount

Reflector color /
Finishing white

#### **Technical drawing**



#### **Temperature limits**

Working temperature -30°C to +50°C Storage temperature -50°C to +80°C


#### **Light control**

ON/off

#### Construction

This Mirror front lamp features a sleek and elegant design with an aluminum housing and a PC cover, offering both aesthetics and durability. The aluminum housing provides excellent heat dissipation, ensuring long life and stable operation of the light. The PC cover delivers soft and even illumination, reducing glare.

### **Photometrics**



#### Warranty

- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)
- For installations where power surge may be possible, NICOR recommends installing additional surge protection at the electrical distribution panel

## **Specifications**













Optilux reserves the right to make changes to this product at any time without notice and such change will be effective immediately. Copyright © 2024 FANGTIAN TECHNOLOGY LLC.