

## MR16 LED Bulbs

Product Code


OPTIMR16W3PA220V

OPTIMR16W3PA220VD



IP rating	20
Ik rating	6
Source type	Hight power LED
Source life time	>50,000h at 25°C ambient temperature
CRI	>80
Step McAdam	3
Source flux	420 lm
Source efficiency	140 lm/W
Delivered flux	330 lm
Delivered efficiency	110 lm/W
Input power	3 W
Supply voltage	DC 12-24V
Insulation Class	insulation class III
Power supply	Built in constant current
Material	Plastic aluminum
Light colour/CCT	2700K/3000K/4000K/6000K
Beam angle	25°/40°/60°
Base	GU5.3
Reflector color	-
Finishing	white

## Technical drawing



## Temperature limits

Working temperature	-30C° to +50C°
Storage temperature	-50C° to +80C°


## Light control

ON/off,Phase dimming

## Construction

The outermost shell is made of plastic, the inside is made of aluminum, and the PC diffusion lampshade


## Photometrics



## Warranty

- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)
- For installations where power surge may be possible, NICOR recommends installing additional surge protection at the electrical distribution panel

## Specifications



OPTILUX LIGHTING

Optilux reserves the right to make changes to this product at any time without notice and such change will be effective immediately.  
Copyright © 2024 FANGTIAN TECHNOLOGY LLC.