

## Datasheet

### A55 Bulbs

#### Product Code


OPTIA55W5PA220V

OPTIA55W5PA220VD



IP rating	20
Ik rating	6
Source type	Hight power LED
Source life time	>50,000h at 25°C ambient temperature
CRI	>80
Step McAdam	3
Source flux	700 lm
Source efficiency	140 lm/W
Delivered flux	550 lm
Delivered efficiency	110 lm/W
Input power	5W
Supply voltage	AC 100-240V
Insulation Class	insulation class III
Power supply	Built in constant current
Material	Plastic aluminum
Light colour/CCT	2700K/3000K/4000K/6000K
Beam angle	240°
Base	E26/E27/B22
Reflector color	-
Finishing	white

## Technical drawing



## Temperature limits

Working temperature	-30C° to +50C°
Storage temperature	-50C° to +80C°


## Light control

ON/off,Phase dimming

## Construction

The outermost shell is made of plastic, the inside is made of aluminum, and the PC diffusion lampshade


## Photometrics



## Warranty

- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)
- For installations where power surge may be possible, NICOR recommends installing additional surge protection at the electrical distribution panel

## Specifications



## OPTILUX LIGHTING

Optilux reserves the right to make changes to this product at any time without notice and such change will be effective immediately.  
Copyright © 2024 FANGTIAN TECHNOLOGY LLC.