OPTILUX

Wall Washer

Product Code OPTOWW682824V



IP rating 66 Ik rating 8

Source type Hight power LED

Source life time >50,000h at 25°C ambient temperature

CRI >80

Step McAdam3Source flux11520 lmSource efficiency120 lm/WDelivered flux8640lmDelivered efficiency90 lm/WInput power96W

Insulation Class insulation class III

Power supply Built in constant current

Material Aluminum+tempered glass


Light colour/CCT 3000K/4000K/6000K/RGB/RGBW


DC24V

Beam angle 15°/30°/60°/10X60°
Mounting surface mount

Reflector color - Grey

Technical drawing





Temperature limits

Working temperature -30°C to +50°C Storage temperature -50°C to +80°C


Light control


ON/off,DMX 512


Construction


Aluminum lamp body, tempered glass face mask; The lens angle can be selected; The protection level reaches IP66; Surface anodizing or powder electrostatic spraying, the appearance can be customized according to the color of the curtain wall, allowing the product to better integrate into the building.

Photometrics









Warranty

- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)
- For installations where power surge may be possible, NICOR recommends installing additional surge protection at the electrical distribution panel

Specifications















OPTILUX LIGHTING