

Surface mounted spotlights


Product Code
OPTOSL11CR30W220V



Technical drawing



Photometrics



| | |
|----------------------|--------------------------------------|
| IP rating | 65 |
| Ik rating | 8 |
| Source type | High power LED |
| Source life time | >50,000h at 25°C ambient temperature |
| CRI | >80 |
| Step McAdam | 3 |
| Source flux | 3600 lm |
| Source efficiency | 120 lm/W |
| Delivered flux | 2400 lm |
| Delivered efficiency | 80 lm/W |
| Input power | 30W |
| Supply voltage | 110~240V AC |
| Insulation Class | insulation class III |
| Power supply | Built in constant current |
| Material | aluminium |
| Light colour/CCT | 3000K/4000K/6000K |
| Beam angle | 60° |
| Mounting | surface mount |
| Reflector color | black |
| Finishing | Grey/Black |

Temperature limits

| | |
|---------------------|----------------|
| Working temperature | -30C° to +50C° |
| Storage temperature | -50C° to +80C° |

Light control

ON/off

Construction

Die cast aluminum shell, surface sandblasting treatment, anti-corrosion and rust prevention, adjustable bracket, tempered glass, stainless steel screws

Warranty

- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)
- For installations where power surge may be possible, NICOR recommends installing additional surge protection at the electrical distribution panel

Specifications

