## **OPTILUX**

## Landscape Tree Lights

Product Code
OPTOSL2DS64\*2W220VA



# IP rating 65 Ik rating 8

**Source type** Hight power LED

**Source life time** >50,000h at 25°C ambient temperature

CRI >80 Step McAdam 3

Source flux

Source efficiency

Delivered flux

Delivered efficiency

Input power

15360 Im

120 Im/W

10240 Im

80 Im/W

128W

Supply voltage 110~240V AC Insulation Class III


Power supply Built in constant current


Material aluminium

Light colour/CCT3000K/4000K/6000KBeam angle12°/24°/36°/60°Mountingsurface mount

**Reflector color** black **Finishing** Grey

## Technical drawing





## **Temperature limits**

Working temperature -30°C to +50°C Storage temperature -50°C to +80°C


## **Light control**

ON/off

#### Construction

Die cast aluminum shell, surface sandblasting treatment, anticorrosion and rust prevention, tempered glass, stainless steel screws, adjustable angle  $\pm$  70 °

#### **Photometrics**



#### Warranty

- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)
- For installations where power surge may be possible, NICOR recommends installing additional surge protection at the electrical distribution panel

## **Specifications**















#### **OPTILUX LIGHTING**