


Wall Light

Product Code
OPTIWL5AS12W220V
OPTIWL5AS12W220VD



IP rating	65
Ik rating	6
Source type	High power LED
Source life time	>50,000h at 25°C ambient temperature
CRI	>80
Step McAdam	3
Source flux	1440 lm
Source efficiency	120 lm/W
Delivered flux	960 lm
Delivered efficiency	80 lm/W
Input power	12W
Supply voltage	110~240V AC
Insulation Class	insulation class III
Power supply	Built in constant current driver
Material	aluminum+Acrylic
Light colour/CCT	3000K
Beam angle	diffuse
Mounting	surface mount
Reflector color	-
Finishing	Black

Technical drawing



Temperature limits

Working temperature	-30C° to +50C°
Storage temperature	-50C° to +80C°


Light control

ON/OFF,DALI Dimming

Construction

Die cast aluminum shell, surface sandblasting treatment, Double layer acrylic lampshade, stainless steel screws


Photometrics



Warranty

- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)
- For installations where power surge may be possible, NICOR recommends installing additional surge protection at the electrical distribution panel

Specifications





Optilux reserves the right to make changes to this product at any time without notice and such change will be effective immediately.
Copyright © 2024 FANGTIAN TECHNOLOGY LLC.