#### Datasheet

# Path light

### Product Code OPTOPL11A50W220V



**IP** rating Ik rating Source type Source life time CRI Step McAdam Source flux Source efficiency **Delivered flux** Delivered efficiency Input power Supply voltage **Insulation Class** Power supply Material Light colour/CCT Beam angle Mounting Reflector color Finishing

65 8 Hight power LED >50,000h at 25°C ambient temperature >90 3 6000 lm 120 lm/W 4000 lm 80 lm/W 50W 110~240V AC insulation class III built-in driver constant current aluminum 4000K 120° post top Matte black

## **Technical drawing**



## **Temperature limits**

Working temperature-30Storage temperature-50

-30C° to +50C° -50C° to +80C°


## **Light control**

ON/off

## Construction

aluminum material with powder coating on the surface,PC diffusion cover, stainless steel screws

## **Photometrics**




## Warranty

- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)
- For installations where power surge may be possible, NICOR recommends installing additional

surge protection at the electrical distribution panel

# Specifications



#### **OPTILUX LIGHTING**

Optilux reserves the right to make changes to this product at any time without notice and such change will be effective immediately. Copyright © 2024 FANGTIAN TECHNOLOGY LLC.

