OPTILUX

Outdoor Recessed Wall Foot Light

Product Code
OPTOFTL4AS6W220V



IP rating 65
Ik rating 8

Source type Hight power LED

Source life time >50,000h at 25°C ambient temperature

CRI >80
Step McAdam 3
Source flux 720 lm
Source efficiency 120 lm/W
Delivered flux 480 lm
Delivered efficiency 80 lm/W
Input power 6W

Supply voltage 110~240V AC Insulation Class insulation class III constant current driver

Material aluminium

Light colour/CCT 3000K/4000K/6000K

Beam angle diffuse

Mounting Recessed Wall Mounting

Reflector color -

Finishing white/black

Technical drawing

65mm 62mm

Wall Cutout Size: 195*50*62mm

Temperature limits

Working temperature -30°C to +50°C Storage temperature -50°C to +80°C


Light control

ON/off

Construction

This outdoor recessed wall foot light features a diffused reflection design, providing soft, glare-free illumination for enhanced visual comfort. With a durable die-cast aluminum housing and IP65 waterproof rating, it ensures long-lasting performance in outdoor environments.

Photometrics



Warranty

- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)
- For installations where power surge may be possible, NICOR recommends installing additional surge protection at the electrical distribution panel

Specifications















OPTILUX LIGHTING