

Outdoor Recessed Wall Foot Light

Product Code OPTOFTL1AS3W220V




Technical drawing





Photometrics



IP rating Ik rating Source type Source life time CRI Step McAdam Source flux Source efficiency **Delivered flux Delivered efficiency** Input power Supply voltage **Insulation Class** Power supply Material Light colour/CCT Beam angle Mounting Reflector color Finishing

65 8 Hight power LED >50,000h at 25°C ambient temperature >80 3 360 Im 120 lm/W 240 Im 80 lm/W 3W 110~240V AC insulation class III constant current driver aluminium 3000K/4000K/6000K diffuse **Recessed Wall Mounting** white/black/Grey

Temperature limits

Working temperature	-30C° to +50C°
Storage temperature	-50C° to +80C°

Light control

ON/off

Construction


This outdoor recessed wall foot light features a diffused reflection design, providing soft, glare-free illumination for enhanced visual comfort. With a durable die-cast aluminum housing and IP65 waterproof rating, it ensures long-lasting performance in outdoor environments.

Warranty

- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)
- For installations where power surge may be possible, NICOR recommends installing additional

surge protection at the electrical distribution panel

Specifications



OPTILUX LIGHTING

Optilux reserves the right to make changes to this product at any time without notice and such change will be effective immediately. Copyright © 2024 FANGTIAN TECHNOLOGY LLC.