
# High Bay Light


#### Product Code OPTOHBL8GR150W220V



## **Technical drawing**



#### **Photometrics**



**IP** rating Ik rating Source type Source life time CRI Step McAdam Source flux Source efficiency **Delivered flux Delivered efficiency** Input power Supply voltage **Insulation Class** Power supply Material Light colour/CCT Beam angle Mounting Reflector color Finishing

65 8 Hight power LED >50,000h at 25°C ambient temperature >80 3 22500 lm 150 lm/W 21000 lm 140 lm/W 150W 110~240V AC insulation class I Philips constant current driver aluminum 3000K/4000K/6000K 90° Suspension installation black

#### **Temperature limits**

Working temperature	-30C° to
Storage temperature	-50C° to

### **Light control**

ON/off,DALI dimming

#### Construction

Die-casting aluminum case, excellent heat dissipation performance, Durable outdoor painting process of the product, excellent quality.anti-corrosion and anti-rusting performance, widely used in different environment


+50C°

+80C°

#### Warranty

- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)
- For installations where power surge may be possible, NICOR recommends installing additional surge protection at the electrical distribution panel

#### Specifications



#### **OPTILUX LIGHTING**

Optilux reserves the right to make changes to this product at any time without notice and such change will be effective immediately. Copyright © 2024 FANGTIAN TECHNOLOGY LLC.

