


Solar Street Light

Product Code
OPTOSSL13GS100W



IP rating	65
Ik rating	8
Source type	Hight power LED
Source life time	>50,000h at 25°C ambient temperature
CRI	>70
Step McAdam	3
Solar panels	5V/10W solar panel
Solar panel type	Polycrystalline silicon
Battery capacity	3.2V/10Ah high-temperature resistant LiFePO4 battery
Working hours	Battery fully charged for over 10 hours
Working mode	Always On
Material	Aluminium+PC
CCT	3000K/4000K/6000K
Beam angle	70°x140°
Mounting	Post top
Reflector color	Grey
Finishing	Grey

Technical drawing



Temperature limits

Working temperature	-30C° to +80C°
Storage temperature	-50C° to +80C°


Light control

Light control/Radar sensor

Construction

The solar street light combines a die-cast aluminum alloy housing with integrated solar panels for corrosion resistance and energy efficiency, along with modular battery compartments, adjustable brackets, and IP65 waterproof design to ensure durability and simple installation in harsh conditions.

Photometrics



Warranty

- 3-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)

Specifications

IP 65	IK 08	Ra>70	ON OFF	Solar	CE
-------	-------	-------	-----------	-------	----