# **OPTILUX**

## Solar Garden Light

Product Code
OPTOSGL14GS30W



IP rating 65
Ik rating 8

Source type Hight power LED

**Source life time** >50,000h at 25°C ambient temperature

CRI >70 Step McAdam 3

**Solar panels** 5V/25W solar panel **Solar panel type** Polycrystalline silicon

Battery capacity

3.2V/25Ah high-temperature resistant

LiFePO4 battery

Working hours Battery fully charged for over 10 hours

Working mode Always On
Material Aluminium+PC
CCT 3000K/4000K/6000K

Beam angle120°MountingPost topReflector colorGreyFinishingGrey


## **Technical drawing**

### **Temperature limits**

Working temperature -30°C to +80°C Storage temperature -50°C to +80°C

## **Light control**


Light control/Radar sensor



#### Construction

The solar garden light combines a die-cast aluminum alloy housing with integrated solar panels for corrosion resistance and energy efficiency, along with modular battery compartments, adjustable brackets, and IP65 waterproof design to ensure durability and simple installation in harsh conditions.

#### **Photometrics**



515mm

#### Warranty

- 3-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)

## **Specifications**













#### **OPTILUX LIGHTING**

Optilux reserves the right to make changes to this product at any time without notice and such change will be effective immediately. Copyright © 2024 FANGTIAN TECHNOLOGY LLC.