

# Solar Street Light

#### **Product Code** OPTOSSL17GS120W



#### **Technical drawing**



#### IP rating 65 8 Hight power LED >50,000h at 25°C ambient temperature >70 3 36V/120W solar panel Polycrystalline silicon 25.6V/20Ah high-temperature resistant LiFePO4 battery Battery fully charged for over 10 hours Always On Aluminium 3000K/4000K/6000K Beam angle 70°x140° Mounting Post top **Reflector color** Grev Finishing Grey

## **Temperature** limits

Working temperature	-30C° to +80C°
Storage temperature	-50C° to +80C°

#### **Light control**

Light control / Radar sensor

## Construction


The solar street light combines a die-cast aluminum alloy housing with integrated solar panels for corrosion resistance and energy efficiency, along with modular battery compartments, adjustable brackets, and IP65 waterproof design to ensure durability and simple installation in harsh conditions.

#### Warranty

• 3-year limited system warranty standard

• Warranty does not cover product failure due to an overvoltage event (power surge)

#### Specifications



#### **OPTILUX LIGHTING**

**Photometrics** 

70°x140°

Optilux reserves the right to make changes to this product at any time without notice and such change will be effective immediately. Copyright © 2024 FANGTIAN TECHNOLOGY LLC.

# ΟΡΤΙLUX

Ik rating Source type Source life time CRI Step McAdam Solar panels Solar panel type **Battery capacity** Working hours Working mode Material ССТ