
# OPTILUX

## Wall Light


Product Code
OPTODL7ES5W220V



## **Technical drawing**



#### **Photometrics**



IP rating 54
Ik rating 0

**Source type** Hight power LED

**Source life time** >50,000h at 25°C ambient temperature

CRI >90
Step McAdam 3
Source flux 600 lm
Source efficiency 120 lm/W
Delivered flux 400 lm
Delivered efficiency 80 lm/W
Input power 5W

Supply voltage 110~240V AC Insulation Class I

**Power supply**Built in constant current

MaterialCopper+CrystalLight colour/CCT2700K/3000K

Beam angle 270°

**Mounting** Surface mount

Reflector color -

Finishing Black/Gold

#### **Temperature limits**

Working temperature -30°C to +50°C Storage temperature -50°C to +80°C

### **Light control**

ON/off,DALI dimming

#### Construction

The wall lamp features a polished solid brass base with anti-oxidation treatment, ensuring long-lasting durability and elegant vintage aesthetics. The handcrafted crystal glass shade diffuses refined light, paired with a universal E14 socket for easy bulb replacement.

### Warranty

- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)
- For installations where power surge may be possible, NICOR recommends installing additional surge protection at the electrical distribution panel

## **Specifications**















#### **OPTILUX LIGHTING**